

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 11.6" Wide Viewing Angle TFT LCD FHD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard
Optional: Rubber keyboard

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 10/100/1000 base-T Ethernet
Intel® Wi-Fi 6E AX211, 802.11ax
Bluetooth (v5.3)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (65W, 100-240VAC, 50/60Hz)
Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimensions (W x D x H) & Weight 313 x 238 x 39mm (12.32" x 9.37" x 1.53")
2.1kg (4.63lbs)

Rugged Feature MIL-STD-810H certified
IP65 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 13.3" Wide Viewing Angle TFT LCD FHD (1920 x 1080)
Protection Film 1,400 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard
Optional: Rubber keyboard

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 10/100/1000 base-T Ethernet
Intel® Wi-Fi 6E AX211, 802.11ax
Bluetooth (v5.3)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (90W, 100-240VAC, 50/60Hz)
Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimensions (W x D x H) & Weight 342 x 281 x 43.9mm (13.46" x 11.06" x 1.37")
2.32kg (5.11lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 13.3" Wide Viewing Angle TFT LCD FHD (1920 x 1080)
Protection Film 1,400 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard
Optional: Rubber keyboard

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 10/100/1000 base-T Ethernet
Intel® Wi-Fi 6E AX211, 802.11ax
Bluetooth (v5.3)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (90W, 100-240VAC, 50/60Hz)
Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimensions (W x D x H) & Weight 342 x 281 x 43.9mm (13.46" x 11.06" x 1.37")
2.32kg (5.11lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 14" TFT LCD HD (1366 x 768)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR4
Optional: 16GB / 32GB / 64GB DDR4
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard
Optional: Rubber keyboard

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 10/100/1000 base-T Ethernet
Intel® Wi-Fi 6E AX211, 802.11ax
Bluetooth (v5.3)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (90W, 100-240VAC, 50/60Hz)
Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimensions (W x D x H) & Weight 350 x 293 x 38.5mm (13.8" x 11.5" x 1.5")
2.38kg (5.25lbs)

Rugged Feature MIL-STD-810H certified
IP63 certified
 MIL-STD-810H certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 15.6" TFT LCD HD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR5
Optional: 16GB / 32GB / 64GB DDR5
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard with integrated numeric keypad

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 15.6" TFT LCD HD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR5
Optional: 16GB / 32GB / 64GB DDR5
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard with integrated numeric keypad

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 15.6" TFT LCD HD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR5
Optional: 16GB / 32GB / 64GB DDR5
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard with integrated numeric keypad

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows 11 Pro
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 15.6" TFT LCD HD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR5
Optional: 16GB / 32GB / 64GB DDR5
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard with integrated numeric keypad

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Operating System Windows Server 2022
Mobile Computing Platform Intel® Core™ Ultra 5 processor
Max. 4.4GHz with Intel® Turbo Boost Technology

Display 15.6" TFT LCD HD (1920 x 1080)
Protection Film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory 8GB DDR5
Optional: 16GB / 32GB / 64GB DDR5
256GB PCIe NVMe SSD

Keyboard & Buttons LED backlit membrane keyboard with integrated numeric keypad

Expansion Slot Smart card reader x 1
Optional: SD card reader x 1
Optional: 1D/2D imager barcode reader

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)**

Security Feature TPM 2.0
 Kensington lock
Smart card reader
Optional: HF RFID reader

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

V110
Units equipped with dual channel memory come with Intel® Xeon® vPro Graphics
Smart card reader, Optional SD card + Smart card reader, and Optional 1D/2D imager barcode reader are mutually exclusive

Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area

Expansion Slot Smart card reader
ExpressCard 54 + PCMCIA Type II
Optional: 2nd ExpressCard 54 or 2nd PCMCIA Type II

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
 Kensington lock
Smart card reader
Intel® vPro™ Technology

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

S410
Units equipped with dual channel memory come with Intel® Xeon® vPro Graphics
Smart card reader, Optional SD card + Smart card reader, and Optional 1D/2D imager barcode reader are mutually exclusive

Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area

Expansion Slot Smart card reader
ExpressCard 54 + PCMCIA Type II
Optional: 2nd ExpressCard 54 or 2nd PCMCIA Type II

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
 Kensington lock
Smart card reader
Intel® vPro™ Technology

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

X600 Pro
The configuration with a discrete graphic controller requires the 230W AC adapter
150W AC adapter is not applicable with discrete graphic controller nor office dock

Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area

Expansion Slot Smart card reader
ExpressCard 54 + PCMCIA Type II
Optional: 2nd ExpressCard 54 or 2nd PCMCIA Type II

I/O Interface SM webcam x 1
Audio in/out combo x 1
DC in Jack x 1

Communication Interface 2.5GBASE-T Ethernet
 Kensington lock
Smart card reader
Intel® vPro™ Technology

Power AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Dimensions (W x D x H) & Weight 412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")
8.145kg (17.95 lbs)

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

Rugged Feature MIL-STD-810H certified
IP66 certified
 MIL-STD-461G certified

Environmental Specification Temperature:-
 -Operating: -29°C to 63°C / -20°F to 145°F
 -Storage: -51°C to 71°C / -60°F to 160°F

ONE BRAND MULTIPLE CHOICES

GETAC TECHNOLOGY CORPORATION
5F, Building A, No. 200, Section 1, Nangang Rd., Nangang Dist., Taipei City 11668, Taiwan, R.O.C.
Tel : +886 2 2785-7888
globalmarketing@getac.com | www.getac.com



Copyright © 2024 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herein is for reference only.
Available specification shall be subjected to customer by request.
V01M06Y24W04

